

Фильтрация по годам

1. Вставляем код решения в ТДС перед вызовом метода show():

```
$oCore_QueryBuilder_Select = Core_QueryBuilder::select("extract( year
from datetime) as res" )
    ->from('informationsystem_items')
    ->where('informationsystem_id', '=',
Core_Array::get(Core_Page::instance()->libParams,
'informationssystemId'))
    ->where('informationsystem_group_id', '=',
$Informationssystem_Controller_Show->group)
    ->where('active', '=', 1)
    ->where('deleted', '=', )
    ->groupby('res')
;
$aYears = $oCore_QueryBuilder_Select->execute()->asAssoc()->result();

$yearsXML = Core::factory('Core_Xml_Entity')->name('years');
foreach ($aYears as $aYear)
{
    $yearsXML->addEntity(
        Core::factory('Core_Xml_Entity')
            ->name('year')->value($aYear['res'])
    );
}

$Informationssystem_Controller_Show->addEntity($yearsXML);
// /KAD

// KAD: фильтрация по годам

$year = (int)Core_Array::getGet("year", );

if ($year)
{
    $datefrom = $year . "-01-01 00:00:00";
    $dateto = ($year+1) . "-01-01 00:00:00";

    if (!$Informationssystem_Controller_Show->item)
    {
$Informationssystem_Controller_Show->informationsystemItems()->queryBuil
der()
        ->where('datetime', '>', $datefrom)
        ->where('datetime', '<', $dateto);

$Informationssystem_Controller_Show->addEntity(Core::factory('Core_Xml_E
ntity')->name('year')->value($year));
```

```
}  
}
```

2. В xsl там где нужен вывод годов, вставляем код:

```
<xsl:for-each select="years/year">  
  <xsl:sort select="." order="descending"/>  
  <a href="?year={.}">  
    <xsl:if test="/informationssystem/year = .">  
      <xsl:attribute  
name="class">active</xsl:attribute>  
    </xsl:if>  
    <xsl:value-of select="."/></a>  
</xsl:for-each>
```